



SAFETY DATA SHEET

Revision Date 24-Apr-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name 14H THREAD SEALANT W/PTFE 4 FL.OZ.

Other means of identification

Product Code 80632

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
10 Columbus Blvd.
Hartford, CT 06106 USA

Distributor

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex
(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Danger

Harmful if swallowed
May cause cancer
Causes damage to organs
Flammable Liquid

**Appearance** White**Physical state** Paste**Odor** Alcoholic**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Do not breathe dust/fume/gas/mist/vapors/spray
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician
 Specific treatment (see supplemental first aid instructions on this label)
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth
 In case of fire: Use Water spray, fog or regular foam for extinction

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects.

Unknown acute toxicity

65.99515% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
TALC	14807-96-6	15 - 40	*
ETHANOL	64-17-5	10 - 30	*
CASTOR OIL	8001-79-4	10 - 30	*
POLYVINYL RESIN	63148-65-2	5 - 10	*
2-PROPANOL	67-63-0	1 - 5	*
TITANIUM DIOXIDE	13463-67-7	1 - 5	*
METHANOL	67-56-1	1 - 5	*
POLYTETRAFLUOROETHYLENE	9002-84-0	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with soap and water. If symptoms persist, call a physician.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store locked up.
Incompatible materials	Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TALC 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
2-PROPANOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
METHANOL 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).
--------------------------	---

Appropriate engineering controls

Engineering Controls	Showers Eyewash stations Ventilation systems
-----------------------------	--

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Paste
Appearance	White
Odor	Alcoholic
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	82 °C / 180 °F	
Flash point	23 °C / 74 °F	
Evaporation rate	< 1	Tag Closed Cup
Flammability (solid, gas)	No information available	Butyl acetate = 1
Flammability Limit in Air		
Upper flammability limit:	12.7%	
Lower flammability limit:	2.3%	
Vapor pressure	33 mm Hg @ 68°F	
Vapor density	>1	Air = 1
Relative density	1.06-1.10	
Water solubility	Partially soluble	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	36.7%
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

Fluorides

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation	Harmful by inhalation.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	May be harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
2-PROPANOL 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg (Rat)	-	-
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TALC 14807-96-6	-	Group 3	-	-
ETHANOL 64-17-5	A3	Group 1	Known	X
2-PROPANOL 67-63-0	-	Group 1	-	X
TITANIUM DIOXIDE 13463-67-7	-	Group 2B	-	X
POLYTETRAFLUOROETHYLENE 9002-84-0	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Contains a known or suspected reproductive toxin.

Target Organ Effects Blood, Central nervous system, Central Vascular System (CVS), Eyes, Gastrointestinal tract (GI), Liver, Lungs, Reproductive System, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1811 mg/kg

ATEmix (dermal) 6521 mg/kg

ATEmix (inhalation-dust/mist) 11.7 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

35.44605% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
TALC 14807-96-6	-	100: 96 h Brachydanio rerio g/L LC50 semi-static	-
ETHANOL 64-17-5	-	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static 10800: 24 h Daphnia magna mg/L EC50
2-PROPANOL 67-63-0	1000: 96 h Desmodemus subspicatus mg/L EC50 1000: 72 h Desmodemus subspicatus mg/L EC50	11130: 96 h Pimephales promelas mg/L LC50 static 9640: 96 h Pimephales promelas mg/L LC50 flow-through 1400000: 96 h Lepomis macrochirus µg/L LC50	13299: 48 h Daphnia magna mg/L EC50
METHANOL 67-56-1	-	28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static	-

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
ETHANOL 64-17-5	-0.32
2-PROPANOL 67-63-0	0.05
METHANOL 67-56-1	-0.77

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHANOL 67-56-1	-	Included in waste stream: F039	-	U154

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ETHANOL 64-17-5	Toxic Ignitable
2-PROPANOL 67-63-0	Toxic Ignitable
METHANOL 67-56-1	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no 1133
Proper shipping name: Adhesives, Limited Quantity (LQ)
Hazard Class 3
Packing Group III
Emergency Response Guide Number 128

IATA

UN/ID no ID 8000
Proper shipping name: Consumer commodity
Hazard Class 9
ERG Code 9L

IMDG

UN/ID no 1133
Proper shipping name: Adhesives, Limited Quantity (LQ)
Hazard Class 3
Packing Group III
EmS-No F-E, S-D

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Not Listed.
ENCS Not Listed.
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECS - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
METHANOL - 67-56-1	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
METHANOL 67-56-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
ETHANOL - 64-17-5	Carcinogen Developmental
TITANIUM DIOXIDE - 13463-67-7	Carcinogen
METHANOL - 67-56-1	Developmental
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
TALC 14807-96-6	X	X	X
ETHANOL 64-17-5	X	X	X
2-PROPANOL 67-63-0	X	X	X
TITANIUM DIOXIDE 13463-67-7	X	X	X
WATER 7732-18-5	-	-	X
METHANOL 67-56-1	X	X	X
POLYTETRAFLUOROETHYLENE 9002-84-0	-	-	X

METHYL ISOBUTYL KETONE 108-10-1	X	X	X
------------------------------------	---	---	---

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
 HMIS (Hazardous Material Information System)

Revision Date 24-Apr-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet