



SAFETY DATA SHEET

1. Identification

Product number 1000008973
Product identifier **BRAKE PARTS CLEANER**
Company information Sprayway, Inc.
1005 S. Westgate Drive
Addison, IL 60101 United States
Company phone General Assistance 1-630-628-3000
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 07
Recommended use Degreaser
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Serious eye damage/eye irritation Category 2A
Reproductive toxicity Category 2
Specific target organ toxicity, single exposure Category 3 narcotic effects
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	80 - 90
Carbon Dioxide		124-38-9	2.5 - 10
n-Heptane		142-82-5	2.5 - 10

Chemical name	Common name and synonyms	CAS number	%
Solvent naphtha (petroleum), light aliph.		64742-89-8	2.5 - 10
Cyclohexane		110-82-7	0.1 - 1
Toluene		108-88-3	0.1 - 1
Other components below reportable levels			0.01 - 0.1

#: This substance has workplace exposure limit(s).

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 2 Aerosol.

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3
Cyclohexane (CAS 110-82-7)	PEL	5000 ppm 1050 mg/m3
n-Heptane (CAS 142-82-5)	PEL	300 ppm 2000 mg/m3 500 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm

ACGIH

Components	Type	Value
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL TWA	750 ppm 500 ppm
Carbon Dioxide (CAS 124-38-9)	STEL TWA	30000 ppm 5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
n-Heptane (CAS 142-82-5)	STEL TWA	500 ppm 400 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3 30000 ppm
	TWA	9000 mg/m3 5000 ppm
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3 300 ppm
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3 440 ppm
	TWA	350 mg/m3 85 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm
	TWA	375 mg/m3 100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Skin protection

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear. Liquid.

Physical state Gas.

Form Aerosol.

Color clear

Odor	Solvent.
Odor threshold	Not available.
pH	Not applicable estimated
Melting point/freezing point	Not available.
Initial boiling point and boiling range	123.68 °F (50.93 °C) estimated
Flash point	-4.0 °F (-20.0 °C) Concentrate estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1 % estimated
Flammability limit - upper (%)	6.7 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	45 - 60 psig @ 70F estimated
Vapor density	Not available.
Relative density	0.828 g/cm3 estimated estimated
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	474.8 °F (246 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.09 g/cm3 estimated
Flammability class	Flammable IB estimated
Heat of combustion (NFPA 30B)	27.37 kJ/g estimated
Percent volatile	94 % estimated
Specific gravity	0.77 - 0.78 estimated estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Fire or intense heat may cause violent rupture of packages.
Incompatible materials	Acids. Strong oxidizing agents. Aluminum.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged inhalation may be harmful.
Skin contact	Causes mild skin irritation.
Eye contact	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause central nervous system effects.

Information on toxicological effects

Acute toxicity

Narcotic effects. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Product	Species	Test Results
BRAKE PARTS CLEANER (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rat	13340 mg/kg
<i>Inhalation</i>		
LC50	Rat	90 mg/l/4h
Components		
Species		
Test Results		
Acetone (CAS 67-64-1)		
Acute		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l
<i>Oral</i>		
LD50	Rat	5800 mg/kg 2.2 ml/kg
Cyclohexane (CAS 110-82-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 32880 mg/m3, 4 Hours > 5540 ppm, 4 Hours
n-Heptane (CAS 142-82-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 29.29 mg/l, 4 Hours
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 5020 mg/m3, 4 Hours > 4980 mg/m3 > 4980 mg/m3, 4 Hours > 4.96 mg/l, 4 Hours

Components	Species	Test Results
Oral LD50	Rat	4820 mg/kg
Toluene (CAS 108-88-3)		
Acute		
Dermal LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours 12.5 - 28.8 mg/l, 4 Hours
Oral LD50	Rat	5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes mild skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity May damage fertility or the unborn child. Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness. May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Product	Species	Test Results
BRAKE PARTS CLEANER (CAS Mixture)		
Aquatic		
Algae	IC50	Algae 47569 mg/L, 72 Hours
Crustacea	EC50	Daphnia 16290 mg/L, 48 Hours
Fish	LC50	Fish 6585 mg/L, 96 Hours
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours

Components	Species	Test Results
Cyclohexane (CAS 110-82-7)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 23.03 - 42.07 mg/l, 96 hours
n-Heptane (CAS 142-82-5)		
Aquatic		
Fish	LC50	Mozambique tilapia (<i>Tilapia mossambica</i>) 375 mg/l, 96 hours
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Aquatic		
Algae	IC50	Algae 4700 mg/L, 72 Hours
Toluene (CAS 108-88-3)		
Aquatic		
Algae	IC50	Algae 433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 7.645 mg/L, 48 Hours
		Water flea (<i>Daphnia magna</i>) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (<i>Oncorhynchus kisutch</i>) 8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Cyclohexane	3.44
n-Heptane	4.66
Toluene	2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1)	U002
Cyclohexane (CAS 110-82-7)	U056
Toluene (CAS 108-88-3)	U220

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1

Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

Cyclohexane (CAS 110-82-7)

Listed.

Toluene (CAS 108-88-3)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Cyclohexane	110-82-7	0.1 - 1
Toluene	108-88-3	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532
Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV
Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532
Toluene (CAS 108-88-3) 594

US state regulations

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
Carbon Dioxide (CAS 124-38-9)
Cyclohexane (CAS 110-82-7)
n-Heptane (CAS 142-82-5)
Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
Carbon Dioxide (CAS 124-38-9)
Cyclohexane (CAS 110-82-7)
n-Heptane (CAS 142-82-5)
Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Carbon Dioxide (CAS 124-38-9)
Cyclohexane (CAS 110-82-7)
n-Heptane (CAS 142-82-5)
Toluene (CAS 108-88-3)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
Cyclohexane (CAS 110-82-7)
Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-25-2015

Version # 07

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.