



# MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

**Product number** 206-002  
**Product name** **Specialty Film Cleaner**  
**Effective date** 06-Apr-2011  
**Company information** Sprayway, Inc.  
1005 Westgate  
Addison, IL 60101 United States  
**Company phone** General Assistance 1-630-628-3000  
**Emergency telephone US** 800-424-9300  
**Emergency telephone outside US** 703-527-3887  
**Version #** 06  
**Supersedes date** 26-Oct-2009

## 2. Hazards Identification

**Emergency overview** EXTREMELY FLAMMABLE  
CONTENTS UNDER PRESSURE. Aerosol. Prolonged exposure may cause chronic effects. Contact with eyes may cause irritation. Contact with skin may cause irritation. Will be easily ignited by heat, spark or flames.

**Potential health effects**

**Routes of exposure** Inhalation. Skin contact.

**Eyes** Contact with eyes may cause irritation.

**Skin** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

**Ingestion** Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion.

**Target organs** Central nervous system.

**Chronic effects** May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. Prolonged skin contact may defat the skin and produce dermatitis.

**Signs and symptoms** Narcosis. Defatting of the skin. Irritation.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
Aliphatic Petroleum Solvent	64742-89-8	60 - 70
Propane	74-98-6	20 - 30
Synthetic Isoparaffinic Hydrocarbon	64741-66-8	10 - 15

## 4. First Aid Measures

**First aid procedures**

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Skin contact** Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap.

**Inhalation** Move to fresh air. If symptoms persist, get medical attention.

**Ingestion** Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. Call a physician immediately.

**Notes to physician** Symptoms may be delayed.

## 5. Fire Fighting Measures

<b>Flammable properties</b>	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
<b>Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Water. Water spray. Water fog. Dry chemical. Carbon dioxide (CO <sub>2</sub> ).
<b>Protection of firefighters</b>	
<b>Specific hazards arising from the chemical</b>	Fire may produce irritating, corrosive and/or toxic gases.
<b>Protective equipment and precautions for firefighters</b>	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Cool containers with flooding quantities of water until well after fire is out.

## 6. Accidental Release Measures

<b>Methods for containment</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewers, basements or confined areas.
<b>Methods for cleaning up</b>	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly. After removal flush contaminated area thoroughly with water.

## 7. Handling and Storage

<b>Handling</b>	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.
<b>Storage</b>	Level 3 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Level 3 Aerosol. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

## 8. Exposure Controls / Personal Protection

### Exposure limits

#### ACGIH

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

#### OSHA

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established

### Personal protective equipment

<b>Eye / face protection</b>	Wear chemical goggles.
<b>Skin protection</b>	Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing.
<b>Respiratory protection</b>	Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

## 9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	145.4 °F (62.8 °C) estimated
Color	Clear.
Density	0.6387 g/cm <sup>3</sup> estimated
Flammability (HOC)	42.5495 kJ/g estimated
Flash back	Yes
Flash point	-156 °F (-104.4 °C) Propellant
Form	Liquid. Aerosol.
Freezing point	Not available
Odor	Characteristic.
pH	Not applicable
Physical state	Liquid.
Pressure	45 - 65 psig @ 70F
Solubility	Partially
Specific gravity	0.6388 estimated

## 10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.

## 11. Toxicological Information

Acute effects Acute LD50: 3681 mg/kg estimated, Rat, Dermal

### Component analysis - LD50

#### Toxicology Data - Selected LD50s and LC50s

Aliphatic Petroleum Solvent	64742-89-8	Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h
Synthetic Isoparaffinic Hydrocarbon	64741-66-8	Inhalation LC50 Rat >5.04 mg/L 4 h; Oral LD50 Rat >7000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

Sensitization Not expected to be hazardous by OSHA criteria.

Teratogenicity Not expected to be hazardous by OSHA criteria.

## 12. Ecological Information

Ecotoxicity LC50 estimated, Fish, 96.00 Hours,  
Components of this product have been identified as having potential environmental concerns.

## 13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001.

## 14. Transport Information

### Department of Transportation (DOT) Requirements

#### Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

**IMDG****Basic shipping requirements:**

**Proper shipping name** AEROSOLS  
**Hazard class** 2.1  
**UN number** 1950  
**Additional information:**  
**Packaging exceptions** LTD QTY  
**Item** 5F  
**Labels required** None  
**Transport Category** 2

**IATA****Basic shipping requirements:**

**Proper shipping name** Aerosols, flammable  
**Hazard class** 2.1  
**UN number** 1950  
**Additional information:**  
**Packaging exceptions** LTD QTY  
**Labels required** 2.1



<b>15. Regulatory Information</b>
-----------------------------------

**US federal regulations**

OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly Hazardous Process Safety Standard, 29 CFR 1910.119.  
 This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
 CERCLA/SARA Hazardous Substances - Not applicable.

**Occupational Safety and Health Administration (OSHA)**

**29 CFR 1910.1200 hazardous chemical** Yes

**CERCLA (Superfund) reportable quantity**

None

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Section 302 extremely hazardous substance** No  
**Section 311 hazardous chemical** Yes  
**Hazard categories (311/312)** Immediate Hazard - Yes  
 Delayed Hazard - No  
 Fire Hazard - Yes  
 Pressure Hazard - Yes  
 Reactivity Hazard - No

**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**State regulations****U.S. - Pennsylvania - RTK (Right to Know) List**

Chemical Name	Inventory Number	Status
Aliphatic Petroleum Solvent	64742-89-8	Present
Propane	74-98-6	Present

<b>16. Other Information</b>
------------------------------

**Further information**

HMIS® is a registered trade and service mark of the NPCA.

**HMIS® ratings**

Health: 1  
Flammability: 4  
Physical hazard: 0

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**MSDS sections updated**

Product and Company Identification: Product and Company Identification  
Composition / Information on Ingredients: Ingredients

**Prepared by**

Regulatory Compliance