



Fiberglass/Silicone Coated Dryer Hose

APPLICATIONS:

For hot or cold air handling, fume removal or ventilation from dryers, tanks or enclosures. Low pressure handling of gaseous materials. Our Fiberglass/Silicone series resists extreme temperatures, fungi and ozone. Fair resistance to alkalis, water, oils and solvents.

CHARACTERISTICS:

- Very Flexible at Low Temperatures
- Odor Free in Hot Air Service
- Excellent Electrical Properties
- Color: Orange

DH-4001

Single Ply Silicone Fiberglass

TEMPERATURE RANGE: -65°F to +550°F

1-Ply Silicone/Fiberglass with Spring Steel Wire Helix

DH-2001

Double-Ply Silicone Fiberglass

TEMPERATURE RANGE: -80°F to +600°F

2-Ply Silicone/Fiberglass Encapsulating a Spring Steel Wire Helix

FOR LONGER LENGTHS:

Simply twist sections together and cement with high-temp silicone for any length you need!

It's a great way to eliminate costly scrap pieces.

PART NO.	HOSE I.D.	WORM GEAR CLAMP	PRICE PER 12' SECTION
1-Ply			Sold in 12' sections
DH-4001-0075*	3/4"	PSHC-10	Call for Pricing
DH-4001-0100*	1"	PSHC-12	
DH-4001-0125*	1¼"	PSHC-16	
DH-4001-0150	1½"	PSHC-20	
DH-4001-0175	1¾"	PSHC-24	
DH-4001-0200	2"	PSHC-28	
DH-4001-0250	2½"	PSHC-36	
DH-4001-0300	3"	PSHC-44	
DH-4001-0350*	3½"	PSHC-52	
DH-4001-0400	4"	PSHC-64	
DH-4001-0500*	5"	PSHC-72	
DH-4001-0600*	6"	--	
DH-4001-0800*	8"	--	
DH-4001-1000	10"	--	
DH-4001-1200	12"	--	
2-Ply			Sold in 12' sections
DH-2001-0075*	3/4"	PSHC-10	800-627-1033
DH-2001-0100	1"	PSHC-12	
DH-2001-0125	1¼"	PSHC-16	
DH-2001-0150	1½"	PSHC-20	
DH-2001-0175	1¾"	PSHC-24	
DH-2001-0200	2"	PSHC-28	
DH-2001-0250	2½"	PSHC-36	
DH-2001-0300	3"	PSHC-44	
DH-2001-0350	3½"	PSHC-52	
DH-2001-0400	4"	PSHC-64	
DH-2001-0500	5"	PSHC-72	
DH-2001-0600	6"	--	
DH-2001-0800	8"	--	
DH-2001-1000*	10"	--	
DH-2001-1200*	12"	--	

*Special sizes - restocking charges apply on returns.

Other diameters and longer lengths quoted upon request.

Insulated Dryer Hose



Ideal for Heat Loss Problems!

INNER CORE DUCT: 2-ply Silicone/Fiberglass encapsulating a Spring Steel Wire Helix

OUTER DUCT: Black Neoprene

INSULATION: 1" Thick Fiberglass Between Inner and Outer Duct, Fortified With an Extra Wrap of Urethane Foam — If Space Is a Concern, ½" Insulation is Also Available by Special Order

STANDARD LENGTHS: 12'

TEMPERATURE RANGE: -65°F to +500°F

SIZES: Custom Sizes and Shorter Lengths available by Special Order

COLOR: Black with Orange Inner Core



PART NO.	HOSE I.D.	PRICE EACH
IDH-0150-1	1½"	Call for Pricing
IDH-0134-1	1¾"	
IDH-0200-1	2"	
IDH-0250-1	2½"	
IDH-0300-1	3"	
IDH-0400-1	4"	
IDH-0500-1	5"	
IDH-0600-1	6"	

Return Air Dryer Hose



1-PLY FEATURES:

- Ideal for Dryer Return Air & Low Temperature Dryers
- Economical Flexible Industrial Ducting

CONSTRUCTION: Single-Ply Neoprene-coated Fiberglass with Fiberglass Cord Reinforcement

STANDARD LENGTHS: 12'

TEMPERATURE RANGE: -40°F to +350°F

COLOR: Black

2-PLY FEATURES:

- Maximum Flow and Durability

CONSTRUCTION: Double-Ply Neoprene-coated Fiberglass with enclosed Spring Steel Wire Helix.

STANDARD LENGTHS: 12'

TEMPERATURE RANGE: -65°F to 300°F

COLOR: Black

PART NO.	HOSE I.D.	WORM GEAR CLAMP	PRICE PER 12' SECTION
1-Ply Sold in 12' sections			
RDH-1	1"	PSHC-10	Call for Pricing
RDH-114	1¼"	PSHC-16	
RDH-112	1½"	PSHC-20	
RDH-134	1¾"	PSHC-24	
RDH-2	2"	PSHC-28	
RDH-212	2½"	PSHC-36	
RDH-3	3"	PSHC-44	
RDH-312	3½"	PSHC-52	
RDH-4	4"	PSHC-64	
RDH-5	5"	PSHC-72	
RDH-6	6"	--	
RDH-7	7"	--	
RDH-8	8"	--	
RDH-9	9"	--	
RDH-10	10"	--	
RDH-12	12"	--	



PART NO.	HOSE I.D.	WORM GEAR CLAMP	PRICE PER 12' SECTION
2-Ply Sold in 12' sections			
RDH2-1	1"	PSHC-10	Call for Pricing
RDH2-114	1¼"	PSHC-16	
RDH2-112	1½"	PSHC-20	
RDH2-134	1¾"	PSHC-24	
RDH2-2	2"	PSHC-28	
RDH2-212	2½"	PSHC-36	
RDH2-3	3"	PSHC-44	
RDH2-312	3½"	PSHC-52	
RDH2-4	4"	PSHC-64	
RDH2-5	5"	PSHC-72	
RDH2-6	6"	--	
RDH2-7	7"	--	
RDH2-8	8"	--	
RDH2-9	9"	--	
RDH2-10	10"	--	
RDH2-12	12"	--	