Version 4.0 Revision Date 02/14/2024

Print Date 01/10/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	ZEP WHITE LITHIUM GREASE_16N11_12CT		
Material number	:	0000000000331701		
Manufacturer or supplier's details				
Company	:	Zep Inc.		
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137		
Telephone	:	Compliance Services - 877-428-9937		

Emergency telephone numbers

For SDS Information	:	Compliance Services - 877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	white
Odour	solvent-like

GHS Classification

Flammable aerosols	: Category 1
Gases under pressure	: Liquefied gas
Eye irritation	: Category 2A
Specific target organ toxicity -	: Category 3 (Central nervous system)
single exposure	

GHS label elements

Hazard pictograms	Flame Gas cylinder Exclamation mark
Signal word	: Danger
Hazard statements	 H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	: Prevention:

	Print Date 01/10/2025
No smoking. P211 Do not spray on an open flame or P251 Pressurized container: Do not pie use. P261 Avoid breathing dust/ fume/ gas/ P264 Wash skin thoroughly after handli P271 Use only outdoors or in a well-ven P280 Wear eye protection/ face protect Response: P304 + P340 + P312 IF INHALED: Ren and keep comfortable for breathing. Ca CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse for several minutes. Remove contact le easy to do. Continue rinsing. P337 + P313 If eye irritation persists: G attention. Storage: P403 Store in a well-ventilated place. P410 + P412 Protect from sunlight. Do temperatures exceeding 50 °C/ 122 °F. Disposal:	n flames/hot surfaces. r other ignition source. rce or burn, even after mist/ vapours/ spray. ng. itilated area. ion. nove person to fresh air II a POISON e cautiously with water nses, if present and iet medical advice/ not expose to
	 P211 Do not spray on an open flame or P251 Pressurized container: Do not pie use. P261 Avoid breathing dust/ fume/ gas/ P264 Wash skin thoroughly after handlin P271 Use only outdoors or in a well-ven P280 Wear eye protection/ face protect Response: P304 + P340 + P312 IF INHALED: Rem and keep comfortable for breathing. Cal CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse for several minutes. Remove contact left easy to do. Continue rinsing. P337 + P313 If eye irritation persists: G attention. Storage: P403 Store in a well-ventilated place. P410 + P412 Protect from sunlight. Do temperatures exceeding 50 °C/ 122 °F.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 20 - < 30
acetone	67-64-1	>= 20 - < 30
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 10 - < 20

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
lf inhaled	: Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	: If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15

Version 4.0	Revision Date 02/14/2024	Print Date 01/10/2025
	minutes. If on clothes, remove clothes.	
In case of eye contact	 Rinse immediately with plenty of Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsin If eye irritation persists, consult 	ng.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to If symptoms persist, call a physi Take victim immediately to hosp DO NOT induce vomiting unless physician or poison control cent	cian. ital. s directed to do so by a
Most important symptoms and effects, both acute and delayed	: Effects are immediate and delay Symptoms may include irritation Symptoms of overexposure may dizziness; and confusion. May p paralysis, and convulsions.	, redness, pain, and rash. / include disorientation;
	Effects are dependent on expos contact time). Causes serious eye irritation. May cause drowsiness or dizzin Review section 2 of SDS to see	ess.
Notes to physician	: Treat symptomatically. Sympton	ms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	 Collect contaminated fire extinguishing water separately. Thi must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

Version 4.0

Revision Date 02/14/2024

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Always replace cap after use. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep in a dry, cool and well-ventilated place. Observe label precautions. No smoking. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	

Version 4.0

Revision Date 02/14/2024

Print Date 01/10/2025

			concentration	
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
· · · ·		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Version 4.0	Revision Date 02/14/2024	Print Date 01/10/2025
Respiratory protection	: Use respiratory protection unless a ventilation is provided or exposure that exposures are within recomme	assessment demonstrates
Hand protection Material Remarks	Protective glovesThe suitability for a specific workpla with the producers of the protective	
Eye protection	: Tightly fitting safety goggles Access to clean water to rinse eyes include: eye wash stations or show with pure water.	
Skin and body protection	: Impervious clothing Choose body protection according concentration of the dangerous sub	
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at	the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: white
Odour	: solvent-like
Odour Threshold	: No data available
рН	: Not applicable
Melting point/freezing point	: No data available
Boiling point	: No data available
Flash point	:
	Not applicable
Evaporation rate	: No data available
Flammability (solid, gas, liquid)	: Extremely flammable aerosol.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: not determined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Extremes of temperature and direct sunlight. Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.
		Effects are dependent on exposure (dose, concentration, contact time). Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

ACGIH OSHA NTP cute toxicity <u>Product:</u> Acute dermal toxicity <u>Components:</u> Distillates (petroleum), hydrot	No component of this product present a equal to 0.1% is identified as probable, human carcinogen by IARC. No component of this product present a equal to 0.1% is identified as a carcinog carcinogen by ACGIH.	possible or confirmed
ACGIH OSHA NTP cute toxicity <u>Product:</u> Acute dermal toxicity <u>Components:</u> Distillates (petroleum), hydrot	equal to 0.1% is identified as probable, human carcinogen by IARC. No component of this product present a equal to 0.1% is identified as a carcinog	possible or confirmed
ACGIH OSHA NTP cute toxicity <u>Product:</u> Acute dermal toxicity <u>Components:</u> Distillates (petroleum), hydrot	No component of this product present a equal to 0.1% is identified as a carcinog	at levels greater than or
OSHA NTP cute toxicity <u>Product:</u> Acute dermal toxicity <u>Components:</u> Distillates (petroleum), hydrot	carcinogen by ACGIH.	
NTP cute toxicity <u>Product:</u> Acute dermal toxicity <u>Components:</u> Distillates (petroleum), hydrot	No component of this product present a equal to 0.1% is on OSHA's list of regul	5
<u>Product:</u> Acute dermal toxicity <u>Components:</u> Distillates (petroleum), hydrot	No component of this product present a equal to 0.1% is identified as a known oby NTP.	at levels greater than or
Acute dermal toxicity <u>Components:</u> Distillates (petroleum), hydrot		
<u>Components:</u> Distillates (petroleum), hydrot		
Distillates (petroleum), hydrot	: Acute toxicity estimate : > 5,000 mg/ Method: Calculation method	/kg
	treated light: : LD50 Rat: > 5,000 mg/kg	
Acute inhalation toxicity	: LC50 Rat: > 4.6 mg/l Exposure time: 6 h	
Acute dermal toxicity	: LD50 Rat: > 2,000 mg/kg	
acetone:		
Acute oral toxicity	: LD50 Rat: 5,800 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 132 mg/l Exposure time: 3 h	
	LC50 Rat: 50.1 mg/l	
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg	
	LD50 Rabbit: > 7,426 mg/kg	
kin corrosion/irritation	ED50 (Rabbit: > 1,420 mg/kg	

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

Version 4.0

Revision Date 02/14/2024

Print Date 01/10/2025

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available **Bioaccumulative potential**

Product:

Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: No data available
Partition coefficient: n- octanol/water	: Pow: 2.89
Mobility in soil	
No data available	
Other adverse effects	

No data available

Version 4.0	Revision Date 02/14/2024	Print Date 01/10/2025
Product:		
Regulation	40 CFR Protection of Environme Stratospheric Ozone - CAA Sec Substances	
Remarks	This product neither contains, no with a Class I or Class II ODS as Clean Air Act Section 602 (40 C + B).	s defined by the U.S.
Additional ecological information	: No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

Version 4.0 Revision Date 02/14/2024 Print Date 01/10/2025

SECTION 15. REGULATORY INFORMATION

TSCA list	:	No substances are subject to a Significant New Use Rule.
		No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Flammable (gases, aerosols, liquids, or solids) Gases under pressure Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure)
SARA 302	:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65		
		This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

Version 4.0

Print Date 01/10/2025

SECTION 16. OTHER INFORMATION

Further information

NFPA:

HEALTH	3
FLAMMABILITY	4
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 =Slight, 2 = Moderate, 3 = High

4 = Extreme

HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms	Flame Gas cy linder Exclamation mark
Signal w ord	: Danger:
Hazard statements	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
	Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	
	 Prevention: Keep aw ay from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Use only outdoors or in a w ell-ventilated area. Wear eye protection/face protection. Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unw ell. IF IN EYES: Rinse
	10/10

Version 4.0

Revision Date 02/14/2024

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. **Storage:** Store in a w ell-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. **Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	4.0
Revision Date:	02/14/2024
Print Date:	01/10/2025

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.